

Leantime docker-compose & environment file

docker-compose

```
version: '3.3'

services:
  leantime:
    image: leantime/leantime:latest
    container_name: leantime
    restart: unless-stopped
    env_file: ./env                      # Environment file with settings
    volumes:
      - /mnt/koa-01/leantime/public_userfiles:/var/www/html/public/userfiles    # Volume to store public files, logo
      etc
      - /mnt/koa-01/leantime/userfiles:/var/www/html/userfiles                  # Volume to store private user uploaded
      files
      - /mnt/koa-01/leantime/config/custom.ini:/usr/local/etc/php/conf.d/custom.ini
    # networks:
    #   - leantime-net
    ports:
      - "9090:80"                      # The port to expose and access Leantime
    #networks:
    #   leantime-net:
```

Les dernières images sont disponibles sur le site officiel Docker Hub, accessibles via ce lien :

[Leantime](#)

.env

This is a sample configuration file with all possible configuration options.

If you don't want to maintain a file like this you can pass in all variables via Server Variables

Minimum Configuration, these are required for installation

```
LEAN_PORT=80 # The port to expose and access Leantime
LEAN_APP_URL="" # Base URL, only needed for subfolder installation
LEAN_APP_DIR="" # Base of application without trailing slash (used for cookies), e.g, /leantime
```

```
LEAN_PORT='8081'
```

```
LEAN_DEBUG=0 # Debug flag
```

Database - MySQL container

```
MYSQL_ROOT_PASSWORD='XXXXXXX' # Database password
MYSQL_DATABASE='XXXXXXXX' # Database name
MYSQL_USER='XXXXXXXX' # Database username
MYSQL_PASSWORD='XXXXXXXX' # Database password
```

Database - leantime container

```
LEAN_DB_HOST='192.168.100.5' # Database host
LEAN_DB_USER='XXXXXX' # Database username (needs to be the same as MYSQL_USER)
LEAN_DB_PASSWORD='XXXXXX' # Database password (needs to be the same as MYSQL_PASSWORD)
LEAN_DB_DATABASE='XXXXXX' # Database name (needs to be the same as MYSQL_DATABASE)
LEAN_DB_PORT='3306' # Database port
```

Optional Configuration, you may omit these from your .env file

Default Settings

```
LEAN_SITENAME='Leantime' # Name of your site, can be changed later
LEAN_LANGUAGE='fr-FR' # Default language
LEAN_DEFAULT_TIMEZONE='Europe/Paris' # Set default timezone
LEAN_ENABLE_MENU_TYPE=false # Enable to specify menu on a project by project basis
LEAN_SESSION_PASSWORD='XXXXXXXXXXXXXXXXXXXXXXX' #Salting sessions. Replace with a strong password
LEAN_SESSION_EXPIRATION=28800 # How many seconds after inactivity should we logout?
28800seconds = 8hours
LEAN_LOG_PATH=null # Default Log Path (including filename), if not set /logs/error.log will be used
```

Look & Feel, these settings are available in the UI and can be overwritten there.

```
LEAN_LOGO_PATH='/images/logo.svg' # Default logo path, can be changed later
```

```
LEAN_PRINT_LOGO_URL='/images/logo.jpg'      # Default logo URL use for printing (must be jpg or png
format)
LEAN_DEFAULT_THEME='default'                 # Default theme
LEAN_PRIMARY_COLOR='#1b75bb'                 # Primary Theme color
LEAN_SECONDARY_COLOR='#81B1A8'               # Secondary Theme Color

## Fileuploads

# Local File Uploads
LEAN_USER_FILE_PATH='userfiles/'             # Local relative path to store uploaded files (if not using S3)
LEAN_DB_BACKUP_PATH='backupdb/'              # Local relative path to store backup files, need permission to
write
```

Revision #1

Created 9 March 2024 12:08:32 by MASSON Romain

Updated 9 March 2024 12:18:33 by MASSON Romain